



## 3000 4T 20W-50

Lubricant for 4 Stroke motorcycle engine  
Mineral

### TYPE OF USE

Street & road bikes, trails, off-road bikes... fitted with 4 Stroke engines, integrated gearbox or not, wet or dry clutch, engines with or without catalytic converters.

Other uses: ATVs, mopeds...

### PERFORMANCES

STANDARDS API SL / SJ / SH / SG

PERFORMANCES JALOS MA2 under N° M033MOT151, HARLEY-DAVIDSON MC Meets HARLEY DAVIDSON specifications

Lubricant reinforced with Extreme Pressure additives to guarantee protection and life time of the gears.

High lubricant properties to reduce wear and increase engine durability.

High detergent and dispersant properties to maintain engine cleanliness.

JASO MA2 lubricant to ensure highest friction possible between friction plates of wet clutch and guarantee perfect clutch lock up at start-up, acceleration and full speed.

Easy gear shifting.

### RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to using conditions.

Can be mixed with synthetic or mineral lubricants.

### PROPERTIES

|                 |           |        |
|-----------------|-----------|--------|
| Viscosity grade | SAE J 300 | 20W-50 |
|-----------------|-----------|--------|

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



## 3000 4T 20W-50

Lubricant for 4 Stroke motorcycle engine  
Mineral

|                            |            |                          |
|----------------------------|------------|--------------------------|
| Density at 20°C (68°F)     | ASTM D1298 | 0.883                    |
| Viscosity at 40°C (104°F)  | ASTM D445  | 176.4 mm <sup>2</sup> /s |
| Viscosity at 100°C (212°F) | ASTM D445  | 19.6 mm <sup>2</sup> /s  |
| Viscosity Index            | ASTM D2270 | 128.0                    |
| Pour point                 | ASTM D97   | -27.0 °C / -17.0 °F      |
| TBN                        | ASTM D2896 | 6.2 mg KOH/g             |
| Flash point                | ASTM D92   | 240.0 °C / 464.0 °F      |