



Osyris Y 1000

Oil type rust preventive for short term protection

DESCRIPTION

Osyris Y 1000 is a solvent-free rust preventive designed to provide short term protection, with a residual protection film that provides good lubricity

RECOMMANDATION

- Do not expose the product to direct sunlight, rain, or snow
- Avoid direct contact to the ground, store the drums in racks or on pallets
- Store within the temperature range of 10 °C to 30 °C
- Always keep the drums/packs tightly sealed, to avoid product deterioration

FEATURE > BENEFITS

Free of Solvent > Improved safety and user comfort

Easy to use > Can be easily applied by brush, spray or immersion and easy to remove using Alkaline detergents, solvent or mechanical treatments

Little Odor > Operator friendly

TYPICAL CHARACTERISTICS

Typical characteristics	Methods	Units	Osyris Y 1000
Aspect	-	-	Clear
Density (@ 15 °C)	EN ISO 12185	kg/m ³	840
Viscosity (@ 40 °C)	ISO 3104	mm ² /s	22
Flash point	ISO 2592	°C	206
Film thickness	-	μ	6
Protection period - Indoor	Internal	Months	Upto 1

The characteristics shown in this table are typical values given for illustrative purposes.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com