

Vacuum pump oil

Lubricant for various pumps used in agriculture

APPLICATIONS

Vacuum pump oil is suitable for the lubrication of vacuum pumps used in agriculture:

- ✓ Slurry pumps
- ✓ Vane pumps
- ✓ Screw pumps
- ✓ Roots pumps

ADVANTAGES

Vacuum pump oil exhibits lots of properties:

- ✓ No shear
- ✓ Very good anti-wear properties
- ✓ Anti-corrosion, anti-rust, anti-foam properties
- ✓ No air retention
- ✓ Excellent demulsibility
- ✓ Very good seal compatibility

SPECIFICATIONS

- Before using the product, the equipment's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.
- The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.
- If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

APPROVALS

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at <http://sdstotalms.total.com>. This product should not be used for any purposes other than the ones for which it is intended.

For additional information, contact your local Totalenergies Lubricants representative or visit our web site: <https://lubricants.totalenergies.com>

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded from <https://sdstotalms.total.com>

TYPICAL CHARACTERISTICS

Properties	Units	Standards	Vacuum pump oil
Density at 15°C	kg/m ³	ISO 3675	897
Viscosity at 40°C	mm ² /s	ISO 3104	213
Viscosity at 100°C	mm ² /s	ISO 3104	18.4
Viscosity index	-	ISO 2909	95
Pour point	°C	ISO 3016	-21

For additional information, contact your local Totalenergies Lubricants representative or visit our web site: <https://lubricants.totalenergies.com>

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded from <https://sdstotalms.total.com>