



Osyris DWL 3550

Dewatering type rust preventive, with higher flash point

DESCRIPTION

Osyris DWL 3550 is a solvent deposited fluid for corrosion protection specifically developed to present:

- superior water displacement capability
- medium-term protection
- short drying time
- very low odor.

RECOMMENDATION

- Do not expose the product to direct sunlight, rain, or snow
- Avoid direct contact to the ground, store the drums in racks or on pallets
- Store within the temperature range of 10 °C to 30 °C
- Always keep the drums/packs tightly sealed, to avoid product deterioration

FEATURE > BENEFITS

Fast Drying > Supports faster packaging time, enhancing productivity

Superior Dewatering > Ensures effective removal of moisture, reducing risk of premature corrosion

Easy to use > Can be easily applied by brush, spray or immersion and easy to remove using Alkaline detergents, solvent or mechanical treatments

TYPICAL CHARACTERISTICS

Typical characteristics	Methods	Units	Osyris DWL 3550
Aspect	-	-	Clear
Density (@ 15 °C)	EN ISO 12185	kg/m ³	785
Flash Point	EN ISO 2719	°C	62
Viscosity (@ 40 °C)	DIN 51562	mm ² /s	1.7
Thickness of film	-	µm	1.4

The characteristics shown in this table are typical values given for illustrative purposes.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com