



POWER1 4T 20W-50

Power Protection Formula

Description

Castrol POWER1 4T with Power Sustain Technology™ is designed specifically for bikers who love the exhilaration of riding.

Castrol POWER1 4T with Power Sustain Technology™ manages heat and friction ensuring continuous power delivery and provides on-demand acceleration.

Application

Castrol POWER1 4T is designed to manage heat and friction to provide sustained power delivery and on-demand acceleration.

It is suitable for all 4-stroke motorcycle engines, both carburetor and fuel injected where API SN (or below) and JASO MA or MA2 are recommended.

Advantages

- Manages heat and friction in the engine, to ensure continuous power delivery and gives on-demand acceleration. It is specially formulated to suit long riding conditions.
- POWER1 4T resists oil thickening caused by high temperatures.
- POWER1 4T maintains your bikes performance during long rides.
- Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Castrol POWER1 4T 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.8802
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	18.0
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	6651
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	160
Viscosity Index	ASTM D2270	None	125
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	216

Product Performance Claims

API SN
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

POWER1 4T 20W-50
18 Jan 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com