

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

NEVASTANE MP 1.5

SDS #: 086261

previous revision date : No previous validation

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : NEVASTANE MP 1.5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use of lubricants and greases in open systems - Professional

Grease for incidental food contact

Formulation additives, lubricants and greases - Industrial

General use of lubricants and greases in vehicles or machinery - Industrial General use of lubricants and greases in vehicles or machinery - Professional

Use of lubricants and greases in open systems - Industrial

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00

Fax: +33 (0)1 41 35 84 71

rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Hellas S.A. 74-76 Voriou Ipirou & Konitsis Str.

15125 Maroussi Athens Greece

Tel: +30 213 01 72 100 Fax:+30 210 54 40 344

rm.enco-greece@totalenergies.com

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Albania - Armenia, Georgia - Macedonia - Malta : 112

Cyprus Toxicological Center: 1401

Greece: Κέντρο δηλητηριάσεων: +30 21 07 79 37 77

<u>Supplier</u>

Telephone number: Emergency phone: +44 1235 239670

Revision:2023/06/16 Version: 1 Greece ENGLISH 1/26



SDS #: 086261

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %. This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2,6-di-tert-butyl-p-cresol	REACH #: 01-2119555270-46 01-2119565113-46 EC: 204-881-4 CAS: 128-37-0	≤1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [2]
methanol	EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	<0.1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg	[1] [2]

Revision:2023/06/16 Version: 1 Greece ENGLISH 2/26



SDS#:

086261

STOT SE 1, H370	ATE [Inhalation (vapours)] = 3 mg/l STOT SE 1, H370: C ≥ 10% STOT SE 2, H371: 3% ≤ C < 10%	
See Section 16 for the full text of the H statements declared above.		

Additional information

: Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin contact: Wash skin thoroughly with soap and water or use recognized skin cleanser.

Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Revision:2023/06/16 Version: 1 Greece ENGLISH 3/26



SDS#: 086261

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion

products

: carbon monoxide carbon dioxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other

sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Revision:2023/06/16 Version: 1 **ENGLISH** 4/26 Greece



SDS #: 086261

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/substance	Exposure limit values
2,6-di-tert-butyl-p-cresol	Ministry of Labour and Social Affairs (Greece, 9/2021). TWA: 10 mg/m ³ 8 hours.
methanol	Ministry of Labour and Social Affairs (Greece, 9/2021).
	Absorbed through skin.
	TWA: 200 ppm 8 hours.
	TWA: 260 mg/m ³ 8 hours.
	STEL: 250 ppm 15 minutes.
	STEL: 325 mg/m³ 15 minutes.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be

Revision:2023/06/16 Version: 1 Greece ENGLISH 5/26



SDS #: 086261

required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3,

STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
2,6-di-tert-butyl-p-cresol	DNEL	Long term Dermal	0.25 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.5 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Long term Oral	0.25 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	0.435 mg/	General	Systemic
		Inhalation	m³	population	
	DNEL	Long term	1.76 mg/m ³	Workers	Systemic
		Inhalation			•
methanol	DNEL	Short term Oral	4 mg/kg	General	Systemic
			bw/day	population	1
	DNEL	Long term Oral	4 mg/kg	General	Systemic
			bw/day	population	1
	DNEL	Short term Dermal	4 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	4 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Dermal	20 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Long term Dermal	20 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Short term	26 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	26 mg/m ³	General	Local
		Inhalation	3	population	
	DNEL	Short term	26 mg/m³	General	Systemic
		Inhalation		population	'
	DNEL	Long term	26 mg/m³	General	Systemic
		Inhalation]	population	'
	DNEL	Short term	130 mg/m ³	Workers	Local
		Inhalation		-	
	DNEL	Long term	130 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Short term	130 mg/m ³	Workers	Systemic
	7.,22	Inhalation			
	DNEL	Long term	130 mg/m ³	Workers	Systemic
		Inhalation	1.55 1119,111		3,01011110

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
2,6-di-tert-butyl-p-cresol	Fresh water	199 ng/l	-
• •	Marine water	19.9 ng/l	-
	Fresh water sediment	45819 µg/kg dwt	-
	Soil	53.9 µg/kg dwt	-
	Sewage Treatment	17 µg/l	-
	Plant		
	Marine water sediment	45.82 µg/kg dwt	-
	Secondary Poisoning	16.67 mg/kg	-

8.2 Exposure controls

Revision:2023/06/16 Version: 1 Greece ENGLISH 6/26



Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

SDS#:

086261

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.EN 166

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Hydrocarbon-proof gloves

nitrile rubber Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: None under normal use conditions. If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn (Type A/P1).

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid.
Color : Beige.

 Revision:2023/06/16
 Version: 1
 Greece
 ENGLISH
 7/26



otalEnergies sps #: 086261

Odor : Characteristic.
Odor threshold : Not available.

pH : Not applicable. Product is non-soluble (in water).

Melting point/freezing point : >250°C

Initial boiling point and

boiling range

: Not applicable.

Flash point : Open cup: Not applicable.

Evaporation rate : Not available.

Flammability : Yes.

Lower and upper explosion

limit

: Not applicable.

Vapor pressure : Not applicable.
Vapor density : Not applicable.

Relative density : 0.93

Density : 0.93 g/cm³ [15°C]

Solubility(ies) :

Media	Result
water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/ : >3.5

water

Auto-ignition temperature : Not applicable.

Decomposition temperature : >250°C

Viscosity : Kinematic (40°C): Not applicable.

Particle characteristics

Median particle size : Not available.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials: Strong oxidizing agents

10.6 Hazardous : carbon monoxide decomposition products : carbon dioxide

Revision:2023/06/16 Version: 1 Greece ENGLISH 8/26



SDS #: 086261

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
2,6-di-tert-butyl-p-cresol	LD50 Dermal	Rat	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>6000 mg/kg	-	OECD 401
methanol	LC50 Inhalation Gas.	Rat	145000 ppm	1 hours	-
	LC50 Inhalation Gas.	Rat	64000 ppm	4 hours	-
	LC50 Inhalation Vapor	Rat	3 mg/l	4 hours	-
	LD50 Dermal	Rabbit	300 mg/kg	-	-
	LD50 Oral	Rat	100 mg/kg	-	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
methanol	100	300	64000	3	N/A

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
2,6-di-tert-butyl-p-cresol	Eyes - Cornea opacity	Rabbit	0	-	OECD 405 Read across
	Skin - Edema	Rabbit	0	4 hours	OECD 404

Conclusion/Summary

Skin: Based on available data, the classification criteria are not met.Eyes: Based on available data, the classification criteria are not met.Respiratory: Based on available data, the classification criteria are not met.

Sensitization

Conclusion/Summary :

Skin : Based on available data, the classification criteria are not met.Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/substance	Category	Route of exposure	Target organs
methanol	Category 1	-	-

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Conclusion/Summary: Based on available data, the classification criteria are not met.

Revision:2023/06/16 Version: 1 Greece ENGLISH 9/26



SDS #: 086261

Aspiration hazard

Conclusion/Summary: Based on available data, the classification criteria are not met.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

Revision:2023/06/16 Version: 1 Greece ENGLISH 10/26



SDS #: 086261

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
2,6-di-tert-butyl-p-cresol	Acute EC50 0.48 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute EC50 1440 μg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours	-
	Acute LC50 1.1 mg/l Chronic EC10 0.4 mg/l	Fish - Oryzias latipes Algae - Desmodesmus subspicatus	96 hours 72 hours	OECD 203 OECD 201
methanol	Chronic NOEC 0.07 mg/l Chronic NOEC 0.053 mg/l Acute EC50 16.912 mg/l Marine water	Daphnia - Daphnia magna Fish - Danio rerio Algae - Ulva pertusa	21 days 30 days 96 hours	OECD 211 OECD 210 -
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours	-
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours	-
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours	-
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours	-

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
2,6-di-tert-butyl-p-cresol	OECD 301C	4.5 % - Not readily - 28 days	-	Activated sludge

Conclusion/Summary: Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
2,6-di-tert-butyl-p-cresol	-	-	Not readily

12.3 Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
NEVASTANE MP 1.5	>3.5	-	low
2,6-di-tert-butyl-p-cresol	5.1	1277	high
methanol	-0.77	<10	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product has no soil mobility.

The product is insoluble and floats on water Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

Revision:2023/06/16 Version: 1 Greece ENGLISH 11/26



SDS #: 086261

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

· Yes

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used The following Waste Codes are only

suggestions: 12 01 12*

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	9005	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., MOLTEN (2,6-di-tert-butyl-p-cresol)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

Revision:2023/06/16 Version: 1 Greece ENGLISH 12/26



ADN

SDS#:

086261

: The product is only regulated as a dangerous good when transported in tank

vessels.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in

bulk according to IMO

instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Revision:2023/06/16 Version: 1 **ENGLISH** 13/26 Greece



SDS #: 086261

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

LU - Luxembourg prohibited chemicals in the workplace

Not listed.

Inventory list

Australia inventory (AIIC) : Not determined.

Canada inventory (DSL/NDSL) : At least one component is not listed in DSL but all such

components are listed in NDSL.

China inventory (IECSC) : All components are listed or exempted.

Europe inventory (EC) : All components are listed or exempted.

Japan inventory : Japan inventory (CSCL): All components are listed or

exempted.

Japan inventory (ISHL): Not determined.

New Zealand Inventory of Chemicals (NZIoC) : All components are listed or exempted.

Philippines inventory (PICCS) : Not determined.

Korea inventory (KECI) : Not determined.

Taiwan Chemical Substances Inventory (TCSI) : All components are listed or exempted.

Thailand inventory : Not determined.

Turkey inventory : All components are listed or exempted.
United States inventory (TSCA 8b) : All components are listed or exempted.

Vietnam inventory : Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety

Assessment

: See exposure scenarios

Revision:2023/06/16 Version: 1 Greece ENGLISH 14/26



SDS #: 086261

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level
DMEL = Derived Minimal Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic vPvB = Very Persistent and Very Bioaccumulative PNEC = Predicted No Effect Concentration

LC50 = Median lethal concentration

LD50 = Median lethal dose

OEL = Occupational Exposure Limit VOC = Volatile Organic Compound

UVCB Substance of unknown or Variable composition, Complex reaction products

or Biological material

NOEC No Observed Effect Concentration

QSAR = Quantitative Structure-Activity Relationship

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 3
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 1

Revision:2023/06/16 Version: 1 Greece ENGLISH 15/26



SDS #: 086261

Date of revision : 2023/06/16

previous revision date : No previous validation

Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Revision:2023/06/16 Version: 1 Greece ENGLISH 16/26

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture : 086261 Code

: NEVASTANE MP 1.5 **Product name**

Section 1 - Title

Short title of the exposure

scenario

: Use of lubricants and greases in open systems - Professional

List of use descriptors : Identified use name: Use of lubricants and greases in open systems - Professional Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13

Sector of end use: SU22

Subsequent service life relevant for that use: No. Environmental Release Category: ERC08a, ERC08d

Environmental contributing:

scenarios

Health Contributing

Processes and activities

covered by the exposure

scenarios

scenario

: Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without

exposure to heat), e.g. mold releases, corrosion protection, slideways, Includes associated product storage, material transfers, sampling and maintenance activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 8.Cp.v1

Amounts used : Annual site tonnage (tonnes/year): 27.5

Frequency and duration of IISA

Environment factors not influenced by risk management

: Local freshwater dilution factor: 10 Local marine water dilution factor: 100

: Emission days (days per year) : 365

Other conditions affecting environmental exposure

: Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs consistent with EU

Solvent Emissions Directive requirements): 0

Release fraction to wastewater from process (after typical onsite RMMs and before

(municipal) sewage treatment plant): 0

Release fraction to soil from process (after typical onsite RMMs):0

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil

: Prevent discharge of undissolved substance to or recover from onsite wastewater.

Organizational measures to prevent/limit release from site

: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Conditions and measures related to sewage treatment plant

: Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Date of issue/Date of revision : 3/25/2020

Use of lubricants and greases in open systems - Professional

Conditions and measures related to external treatment of waste for disposal

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment

(environment):

: Used ECETOC TRA model.

Exposure estimation and reference to its source

: Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment

(human):

: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment

that covers this product.

Exposure estimation and reference to its source

: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to
	all sites; thus, scaling may be necessary to define appropriate site-specific risk
	management measures. Further details on scaling and control technologies are
	provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e.,
	RCRs > 1), additional RMMs or a site-specific chemical safety assessment is
	required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then
	users should ensure that risks are managed to at least equivalent levels. For further
	information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

Date of issue/Date of revision : 3/25/2020 18/26

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture Code : 086261

Product name : NEVASTANE MP 1.5

Section 1 - Title

Short title of the exposure

List of use descriptors

scenario

: Formulation additives, lubricants and greases - Industrial

: Identified use name: Formulation additives, lubricants and greases - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a,

PROC08b, PROC09, PROC15 **Sector of end use:** SU03, SU10

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC02

Environmental contributing:

scenarios

Health Contributing

Processes and activities

covered by the exposure

scenarios

scenario

: Industrial formulation of lubricant additives, lubricants and greases. Includes material

transfers, mixing, large and small scale packing, sampling, maintenance.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 2.Ai-l.v1

Amounts used

: Volume manufactured/imported (tonnes/year): 22

Frequency and duration of

use

: Emission days (days per year) : 300

Environment factors not influenced by risk management

: Local freshwater dilution factor: 10 Local marine water dilution factor: 100

Other conditions affecting environmental exposure

: Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): 5.00E.02

Solvent Emissions Directive requirements): 5.00E-02 Release fraction to wastewater from process (after typical onsite RMMs and before

(municipal) sewage treatment plant): 2.00E-01

Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release

: Common practices vary across sites thus conservative process release estimates

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil

: Treat air emission to provide a typical removal efficiency of (%): 70

air emissions and releases to soil Organizational measures to Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.

to be also har god that paiding contact by the

prevent/limit release from site
Conditions and measures

plant

: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Conditions and measures : Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03 related to sewage treatment

Date of issue/Date of revision : 3/9/2020

Formulation additives, lubricants and greases -

20/26

Conditions and measures related to external treatment of waste for disposal

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment

(environment):

: Used ECETOC TRA model.

Exposure estimation and reference to its source

: Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment

(human):

: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment

that covers this product.

Exposure estimation and reference to its source

: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction. Health : Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

information see www.atiel.org/reach/introduction.

Date of issue/Date of revision : 3/9/2020

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture Code : 086261

Product name : NEVASTANE MP 1.5

Section 1 - Title

Short title of the exposure

scenario

: General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : Identified use name: General use of lubricants and greases in vehicles or

machinery - Industrial

Process Category: PROC01, PROC02, PROC08b, PROC09

Sector of end use: SU03

Subsequent service life relevant for that use: No. Environmental Release Category: ERC04, ERC07

Environmental contributing:

scenarios

Health Contributing

covered by the exposure

scenarios
Processes and activities

scenario

: Covers general use of lubricants and greases in vehiculs or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Bi.v1

Amounts used

Frequency and duration of

use

otoro not

Environment factors not influenced by risk management

Other conditions affecting environmental exposure

: Annual site tonnage (tonnes/year): 16.5: Emission days (days per year): 300

: Local freshwater dilution factor : 10 Local marine water dilution factor : 100

: Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): 1.00E-01

Release fraction to wastewater from process (after typical onsite RMMs and before

(municipal) sewage treatment plant): 2.00E-01

Release fraction to soil from process (after typical onsite RMMs): 1

Technical conditions and measures at process level (source) to prevent release

: Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.

Organizational measures to prevent/limit release from site

 Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Conditions and measures related to sewage treatment plant

: Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Date of issue/Date of revision : 3/12/2020

General use of lubricants and greases in vehicles or machinery - Industrial

Conditions and measures related to external treatment of waste for disposal

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment

(environment):

: Used ECETOC TRA model.

Exposure estimation and

: Not available.

reference to its source

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment

(human):

: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment

that covers this product.

Exposure estimation and reference to its source

: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to
Littiioiiiioiit	all sites; thus, scaling may be necessary to define appropriate site-specific risk
	management measures. Further details on scaling and control technologies are
	provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e.,
	RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

Date of issue/Date of revision : 3/12/2020 22/26

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 086261

Product name : NEVASTANE MP 1.5

Section 1 - Title

Short title of the exposure

: General use of lubricants and greases in vehicles or machinery - Professional

scenario

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or

machinery - Professional

Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20

Sector of end use: SU22

Subsequent service life relevant for that use: No. Environmental Release Category: ERC09a, ERC09b

Environmental contributing:

scenarios

Health Contributing

Processes and activities

covered by the exposure

scenarios

scenario

: Covers general use of lubricants and greases in vehiculs or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 9.Bp.v1

Amounts used

: Volume manufactured/imported (tonnes/year) : 27.5

Frequency and duration of

use

: Emission days (days per year) : 300

Environment factors not influenced by risk management

: Local freshwater dilution factor : 10 Local marine water dilution factor : 100

Other conditions affecting environmental exposure

: Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements): 0

Release fraction to wastewater from process (after typical onsite RMMs and before

(municipal) sewage treatment plant): 0

Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release

: Common practices vary across sites thus conservative process release estimates

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil

: Prevent discharge of undissolved substance to or recover from onsite wastewater.

Organizational measures to prevent/limit release from

: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Conditions and measures related to sewage treatment plant

: Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Date of issue/Date of revision : 3/20/2020

General use of lubricants and greases in vehicles or machinery - Professional

Conditions and measures related to external treatment of waste for disposal

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment

(environment):

: Used ECETOC TRA model.

Exposure estimation and reference to its source

: Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment

(human):

: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment

that covers this product.

Exposure estimation and reference to its source

: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
 Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

Date of issue/Date of revision : 3/20/2020 24/26

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture Code : 086261

Product name : NEVASTANE MP 1.5

Section 1 - Title

Short title of the exposure

scenario

: Use of lubricants and greases in open systems - Industrial

List of use descriptors : Identified use name: Use of lubricants and greases in open systems - Industrial Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10,

PROC13

Sector of end use: SU03

Subsequent service life relevant for that use: No. Environmental Release Category: ERC04

Environmental contributing:

scenarios

Health Contributing

Processes and activities

covered by the exposure

scenarios

scenario

: Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Ci.v1

Amounts used

: Annual site tonnage (tonnes/year) : 16.5: Emission days (days per year) : 300

Frequency and duration of use

Environment factors not influenced by risk

influenced by risk management

: Local freshwater dilution factor : 10 Local marine water dilution factor : 100

Other conditions affecting environmental exposure

: Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs consistent with EU

Solvent Emissions Directive requirements): 1.00E-01

Release fraction to wastewater from process (after typical onsite RMMs and before

(municipal) sewage treatment plant): 2.00E-01

Release fraction to soil from process (after typical onsite RMMs): 1

Technical conditions and measures at process level (source) to prevent release

: Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.

Organizational measures to prevent/limit release from site

: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision : 3/24/2020

Use of lubricants and greases in open systems -Industrial

26/26

Conditions and measures related to sewage treatment plant

: Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Conditions and measures related to external treatment of waste for disposal

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment):

: Used ECETOC TRA model.

Exposure estimation and reference to its source

: Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human):

: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment

that covers this product.

Exposure estimation and reference to its source

: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to
	all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are
	provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e.,
	RCRs > 1), additional RMMs or a site-specific chemical safety assessment is
	required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then
	users should ensure that risks are managed to at least equivalent levels. For further
	information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

Date of issue/Date of revision : 3/24/2020