V.01/2023 Ref. 00000000



# Finaturol K2

## Vegetable oil for dough dividers and bread cutting machines

### **APPLICATIONS**

Baking industry.

Finaturol K2 is a vegetable oil used to prevent sticking of the dough and it is also used to prevent sticking of the dough on the knives.

#### **ADVANTAGES**

Finaturol K2 allows to reduce oil consumption up to 20% compared to white mineral oils.

Finaturol K2 increases knives lifetime.

Due to its specific formula, Finaturol K2 does not change taste nor color of the finished product.

#### **SPECIFICATIONS**

Finaturol K2 is a 100% vegetable oil guaranteed GMO free and made without animal products, guaranteed palm oil free. It is made of vegetable oil and food additives which are included in the positive list of the Regulation (CE) n°1333/2008.

Finaturol K2 has the NSF Registration No 131902 Category Code 3H. It may be used in direct contact with food according to USA FDA 21 CFR 182-184.

It meets the European laws concerning food processing aid, most of all the regulation (CE) n°1333/2008.

Finaturol K2 has been approved by French food agency (DGCCRF) for use as a food processing aid in bakery (maximum residual quantity in dough is 3 g/kg).

Finaturol K2 meets Europeans laws 1829/2003/CE et 1830/2003/CE regarding GMO labelling.

Finaturol K2 does not contain any allergenic food ingredient in compliance with the Regulation (CE) n°1169/2011 - INCO.

Finaturol K2 does not intentionally contain MOSH and MOAH.

#### Recommendations:

Store between 0 and 30 °C in a place protected from daylight. Shelf life: 12 months from date of manufacture.

#### TYPICAL CHARACTERISTICS

Properties	Units	Standards	Finaturol K2
Aspect, color	-	Visual	Limpid liquid, clear yellow
Density @ 15°C	kg/m³	ISO 12185	920
Kinematic viscosity @ 40 °C	mm²/s	ISO 3104	35
Acid number	mg KOH/g	ISO 6618	< 0,3
lodine number	g I/100 g	ISO 3961	100

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com