

Planetelf PAG K 40

Synthetic compressor oil PAG for air conditioning systems of vehicles operating with refrigerants R134a and HFO-1234yf

APPLICATIONS

- Planetelf PAG K 40 can be used in most on-board air conditioning systems and provides superior protection while reducing wear.

ADVANTAGES

- High protection against wear
- Good thermal stability
- Compatibility with the internal materials of the compressors
- Good miscibility with HFO-1234yf and R-134a

Approvals

Meets the main specifications of:

- SANDEN
- VALEO
- MAHLE

TYPICAL CHARACTERISTICS

Properties	Units	Standards	Planetelf PAG K 40
Color	-	ASTM D 1500	L0.5
Density at 15°C	kg/m ³	ASTM D 4052	999
Viscosity at 40°C	mm ² /s	ASTM D 445	40
Viscosity at 100°C	mm ² /s	ASTM D 445	8
Pour point	°C	ASTM D 97	< -40
Flash point (COC)	°C	ASTM D 92	> 210

For additional information, contact your local Totalenergies Lubricants representative or visit our web site: <https://lubricants.totalenergies.com>

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded from <https://sds.totalms.total.com>