



Martol EV 10 CF

DESCRIPTION

Whether you need to cut, drill, grind, or form metal parts, TotalEnergies Lubrificants has the right metalworking fluid for you. Our products are designed to meet the highest standards of quality and performance, and to help you optimize your operations.

Martol is a versatile range of high-performance forming fluids, shaping a path of consistency for you and your operations.

APPLICATIONS

Martol EV products are formulated with lightweight hydrocarbon cuts and high-performance additives, reducing, or eliminating the need for degreasing.

Martol EV 10 CF is designed for aluminum and for pressed components produced from 0.2 to 0.5 mm thick blanks which must not be degreased.

RECOMMENDATIONS

Martol EV 10 CF is suitable for light forming operations

- Degreasing possible at room temperature
- Low odour
- Excellent wetting properties
- Applicability by brush, spraying or roller
- Non staining of non-ferrous materials

TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL EV 10 CF
Density at 15 °C	ISO 12185	kg/m ³	764
Colour	visual	-	Transparent
Viscosity at 20°C	ISO 3104	mm ² /s	1.8
Viscosity at 40°C	ISO 3104	mm ² /s	1.3
Flash point (PM)	ISO 2719	°C	> 61°C

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com