



NEVASTANE XS 320

DESCRIPTION

Food grade extreme pressure calcium sulfonate complex grease.



No MOAH* (mineral Oil Aromatic Hydrocarbons) in our grease

* Test realized in external laboratory

SPECIFICATIONS

- **NEVASTANE XS 320** is formulated in accordance with US FDA Regulation 21 CFR, 178.3570.
- **NEVASTANE XS 320** is **NSF H1** registered: No 147141 and ISO 21469 certified.
- ISO 6743-9 : L-XCFFB1/2
- DIN 51 502 : KP1/2R-35

APPLICATIONS

- **NEVASTANE XS 320** is an extreme pressure grease dedicated to the lubrication in food industry under very severe conditions: water, high load, high temperature, dust...
- **NEVASTANE XS 320** is recommended for the lubrication of pelleting presses (KAHL, Promill Stolz, CPM, UMT, Van Aarsen...) in feed and sugar industries.

ADVANTAGES

- **NEVASTANE XS 320** meets the most stringent industrial requirements:
- Continuation of the equipment life while reducing contamination problems as required by the Hazard Analysis and Critical Control Point System (HACCP).
- Excellent mechanical and thermal stability (high dropping point).
- Remarkable load resistance thanks to its naturally high extreme pressure and anti-wear properties.
- Outstanding water and steam resistance and excellent food acids/alkalis resistance.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at ms-sds.totalenergies.com

- No significant loss of consistency is observed even with high amounts of water entering the grease.
- Excellent anti-oxidation and anti-corrosion properties, also in the presence of salt water.

RECOMMENDATIONS

- Store the product at temperatures between 0 and 35°C.
- Shelf life: 36 months from date of manufacture (unopened).

TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	NEVASTANE XS 320
Soap/thickener	-	-	Calcium Sulfonate Complex
Color	Visual	-	Light brown
Appearance	Visual	-	Smooth
NLGI grade	ASTM D 217	grade	1.5
Operating temperature range	-	°C	from -40 to 180
Penetration at 25 °C	ASTM D 217	0.1 mm	280-310
Four ball weld load	ASTM D 2596	kgf	>400
Anti-rust performance SKF-EMCOR	ISO 11007	rating	0 - 0
Dropping point	IP 396	°C	> 300
Base oil type	-	-	White oil / PAO (with polymers)
Kinematic viscosity at 40 °C	ISO 3104	mm ² /s	320

Above characteristics are mean values given as an information.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at ms-sds.totalenergies.com