



# COPAL GEP 0

## DESCRIPTION

Extreme-pressure water resistant high temperature aluminium complex grease with solid lubricants.

## SPECIFICATIONS

ISO 6743-9: L-XBDHB 0

DIN 51 502: OGPFO-N - 20

## APPLICATIONS

**COPAL GEP 0** is pre-eminently designed for use on open gears of rotary drum drives, single and double pinion kiln and mill drives, working under severe circumstances.

## ADVANTAGES

Excellent thermal stability.

Remarkable load resistance thanks to its naturally high extreme pressure and anti-wear properties.

Sprayable, very good adhesion to metals.

Very good water resistance.

Excellent anti-oxidation and anti-corrosion properties thanks to the carefully selected additives.

**COPAL GEP 0** does not contain lead, or other heavy metals considered harmful to human health and the environment.

## RECOMMENDATIONS

Always avoid contamination of the grease by dust and/or dirt when applying.

Preferably use a pneumatic pump/spray system.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser [www.quick-fds.com](http://www.quick-fds.com).

TotalEnergies Lubricants

SA 552 006 454 RCS Nanterre - France

## TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	COPAL GEP 0
Soap/thickener		-	Aluminium complex
NLGI grade	ASTM D 217/DIN 51 818	-	0
Color	Visual	-	Black
Appearance	Visual	-	Smooth/Buttery
Operating temperature range		°C	-20 to 150
Penetration at 25°C	ASTM D 217/DIN51 818	0.1 mm	355-385
Four ball weld load	DIN 51 350-4	daN	580-600
FZG A2.8/50 scuffing load step	DIN 51 354	rating	>12
Weight loss	DIN 51 354	mg/KWh	0,49
Anti-rust performance SKF- EMCOR	DIN 51 802/IP220/NFT 60-135/ISO 11007	rating	0-0
Dropping point	IP 396/NFT 60 102 C	°C	>190
Kinematic viscosity of the base oil at 40°C	ASTM D 445/DIN 51 562-1/ISO 3104/ IP71	mm <sup>2</sup> /s (cSt)	750

Above characteristics are mean values given as an information.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser [www.quick-fds.com](http://www.quick-fds.com).

**TotalEnergies Lubricants**

SA 552 006 454 RCS Nanterre - France