



Martol LVG 15 CF

DESCRIPTION

Whether you need to cut, drill, grind, or form metal parts, TotalEnergies Lubrificants has the right metalworking fluid for you. Our products are designed to meet the highest standards of quality and performance, and to help you optimize your operations.

Martol is a versatile range of high-performance forming fluids, shaping a path of consistency for you and your operations.

APPLICATIONS

Martol LVG products are formulated with lightweight hydrocarbon cuts and high-performance additives, reducing, or eliminating the need for degreasing.

Martol LVG 15 CF is an evaporating oil designed for drawing and stamping operations on aluminum for a thickness < 1 mm.

RECOMMENDATIONS

Martol LVG 15 CF has very low residue level.

- Thermal degreasing at intermediate temperature, ca. 150 °C
- Applicability by brush, spraying or roller
- Superior additivation allowing a wide range of operation
- Compatible with non-ferrous and ferrous materials

TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL LVG 15 CF
Appearance	Visual	-	clear liquid
Density at 15°C	ISO 3675	kg/m ³	765
Colour	Visual	-	colourless
Viscosity at 20°C	ISO 3104	mm ² /s	1.8
PM Flash point	ISO 2719	°C	> 60

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com