



Finadet SW

DESCRIPTION

Finadet detergents are designed to clean production areas and can be used for difficult cleaning.

Finadet SW is a special detergent for washing machines

APPLICATIONS

- Cleaning mechanical components
- Pure or diluted, according to degree of soiling

PERFORMANCES

- Very powerful rejecting detergent for grease and scale removal.
- It can be used cold or hot, by low, medium and high pressure spraying.
- No foaming.
- Anticorrosion properties from 2 % in water, it protects the cleaned parts between operations.
- It can be used for dipping in combination with ultrasonic cleaning.

ADVANTAGES

- **Finadet SW** is a washing product. The absence of flash point ensures optimal safety conditions.
- Without chlorinated molecules.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com

TYPICAL CHARACTERISTICS

Typical characteristics	Methods	Units	Finadet SW
Appearance	Visual		Clear
Colour	Visual		Yellow
Physical state	Visual		Liquid
Density at 25 °C	NF EN ISO 12185	kg/m ³	1056
Odour	Olfactory		none
pH at 5 %	-		8.6
pH pure at 20 °C	-		9.2
Pour point	ISO 3016	°C	- 6
Refraction index	ASTM D 1218		1.4220
Surface tension at 5 % at 25 °C	ISO 6295	dynes/cm	29

The characteristics shown in this table are typical values given for illustrative purposes.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com