



Osyris X 9100

Solvent deposited varnish type rust preventive for long term outdoor storage

DESCRIPTION

Osyris X 9100 is a solvent deposited – varnish type protection fluid designed to protect metal surfaces in harsh conditions like, direct exposure to corrosive fume or maritime operations

RECOMMENDATION

- Do not expose the product to direct sunlight, rain, or snow
- Avoid direct contact to the ground, store the drums in racks or on pallets
- Store within the temperature range of 10 °C to 30 °C
- Always keep the drums/packs tightly sealed, to avoid product deterioration

FEATURE > BENEFITS

Fast Drying > Supports faster packaging time, enhancing productivity

Easy to use > Can be easily applied by brush, spray or immersion and easy to remove using Alkaline detergents, solvent or mechanical treatments

Persistent film > Strong varnish film that is not easily removed by mechanical forces. Film can be removed using Solvent batch

TYPICAL CHARACTERISTICS

Typical characteristics	Methods	Units	Osyris X 9100
Aspect	-	-	Cloudy
Density (@ 15 °C)	EN ISO 12185	kg/m ³	865
Flash Point	EN ISO 2719	°C	42
Viscosity (@ 40 °C)	DIN 51562	mm ² /s	60
Thickness of film	-	µm	42

The characteristics shown in this table are typical values given for illustrative purposes.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com