



Nevastane Penetrating Spray Oil

DESCRIPTION

Multipurpose, NSF-H1-certified penetrating and releasing oil – Contains lubricity, anti-seizing, anti-corrosion, and water repellent agents.

Keep away from daylight, dust, and humidity.

Shelf life: 2 years from date of manufacture.

CAUTION

Due to the container and the presence of solvents:

Keep away from heat, sparks, and flames.

Do not expose to heat and temperatures exceeding 50°C.

Even when empty, do not puncture or incinerate the container.

APPLICATIONS

- Multi-effect penetrating fluid: Releases rusted mechanisms, drives water out, protects against corrosion
- To be used on mechanisms in the food industry (hot, wet and/or corrosive atmospheres)
- Food Industry, canneries, bakeries, abattoirs, processing plants...

ADVANTAGES

- High penetrating power
- High wetting power
- Non-flammable propellant gas: CO₂
- Can be used upside-down for an easier manipulation of the spray

TYPICAL CHARACTERISTICS

PROPERTIES	Nevastane Penetrating Oil Spray	UNITS	STANDARDS
Color	Pale yellow	-	Visual
Appearance	Limpid liquid	-	Visual
Density at 20°C	770	kg/m ³	ISO 3675
Freezing point	-30	°C	ASTM D 2386

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded at www.quick-fds.com.